


MATERIAL SAFETY DATA SHEET

POLAROID CORPORATION
OFFICE OF HEALTH, SAFETY, & ENVIRONMENTAL AFFAIRS
1265 MAIN STREET - WALTHAM, MA 02254
(781) 386-0879

Data Sheet No. M-0917	Revision I	NFPA FIRE HAZARD SYMBOL
		
Compiled by: E. Karger	Issue Date: 08-JUN-1998	

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

COMMON NAMES: DEVELOPER FLUID CONTAINED IN POD OF FILM TYPES 338;
POLAROID 600 BLACK & WHITE; POLAROID 600 EXTREME
MONOCHROME

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL FAMILY: MIXTURE

INGREDIENTS

Please note that chemicals present in the mixture in concentrations below 1% which are considered not to be a hazard may not be included in the list of ingredients

Material	%	MSDS#	CAS#	PL# /Comments
POTASSIUM HYDROXIDE	5-10		001310-58-3	
TITANIUM DIOXIDE; RUTILE; TI-PURE TITANIUM DIOXIDE PIGMENT	30-60		013463-67-7	
DMEHA; DI (METHOXYETHYL) HYDROXYLAMINE	1-3		005815-11-2	
6-METHYLURACIL	0.10-1		000626-48-2	
5-METHYLURACIL; THYMINE	0.10-1		000065-71-4	
SNP22E; SNP22K	1-3			
LUDOX, HS-30, HS-40; NALCOAG 1034-A, NALCO 2327; NYACOL 1430-LS, 5050, 9050	1-3		007631-86-9	

INGREDIENTS (CONT.)

Material	%	MSDS#	CAS#	PL# /Comments
URACIL	1-3		000066-22-8	
WATER	10-30		007732-18-5	

SECTION III - HAZARDS IDENTIFICATION

Hazard Signal Word

WARNING

Hazards

CONTAINS ALKALI

Eye Contact May Cause Permanent Eye Damage.

Skin and Mouth Contact May Cause Irritation or Burns.

Precautionary Measures

Do not get in eyes, on skin, mouth or clothing.

Wash thoroughly after handling

INGREDIENT EXPOSURE LIMITS

POTASSIUM HYDROXIDE

OSHA Permissible Exposure Limit: PEL/TWA 2 mg/m3 (ceiling)

ACGIH TLV/TWA 2 mg/m3 (ceiling)

TITANIUM DIOXIDE; RUTILE; TI-PURE TITANIUM DIOXIDE PIGMENT

OSHA Permissible Exposure Limit: PEL/TWA 10 mg/m3 (Total Dust) 5 mg/m3 (Respirable Fraction)

ACGIH TLV/TWA 10 mg/m3

IDLH IDLH 5000 mg/m3

DMEA; DI(METHOXYETHYL)HYDROXYLAMINE

OSHA Permissible Exposure Limit: PEL/TWA None established

ACGIH TLV/TWA Not listed

6-METHYLURACIL

OSHA Permissible Exposure Limit: PEL/TWA None established

ACGIH TLV/TWA Not listed

5-METHYLURACIL; THYMINE

OSHA Permissible Exposure Limit: PEL/TWA None established

ACGIH TLV/TWA Not listed

DEVELOPER FLUID CONTAINED IN POD OF FILM TYPES 338; POLAROID 600 BLACK & WHITE; POLAROID 600 EXTREME MONOCHROME

SECTION VII - HANDLING AND STORAGE

Not Available

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

RECOMMENDED VENTILATION:

Not normally required.

RESPIRATORY PROTECTION:

Not normally required.

EYE PROTECTION:

Not normally required.

SKIN PROTECTION:

Not normally required.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Cream, white, tan, grey or pink viscous fluid

Melting Point: ND
Boiling Point: @ 760 mm Hg: 100 °C (212°F) (Water)
Specific Gravity(H₂O=1): 1.1
% Solubility in Water: @ 20°C: dilutable
Vapor Density (AIR=1): ND
% Volatiles by volume: 85 (approximate)
Vapor Pressure: ND
Evaporation Rate: (Butyl Acetate=1): < 1
pH: > 13 - drops rapidly after processing
Pour Point: ND
Softening Point: ND
Viscosity: ND
Bulk Density: ND
Surface Tension: ND
Log Kow: ND

SECTION X - STABILITY AND REACTIVITY

Hazardous Reactivity:

Mixture is considered stable.

SECTION XI - TOXICOLOGICAL INFORMATION

INHALATION:

May be an irritant

SKIN CONTACT:

Corrosive

EYE:

Corrosive

INGESTION:

Corrosive

DEVELOPER FLUID CONTAINED IN POD OF FILM TYPES 338; POLAROID 600 BLACK & WHITE; POLAROID 600 EXTREME MONOCHROME

SECTION XI - TOXICOLOGICAL INFORMATION (CONT.)

Effects of Acute Overexposure:

Eye contact with developer may cause permanent eye damage. May cause burns to skin and mouth.

Effects of Chronic Overexposure:

None currently known.

SECTION XII - ECOLOGICAL INFORMATION

Not Available

SECTION XIII - DISPOSAL CONSIDERATIONS

Product (film pack, picture) is not classified or regulated under U.S. federal law as "RCRA Hazardous" before or after processing.

SECTION XIV - TRANSPORT INFORMATION

OTHER D.O.T. INFORMATION

Film product not regulated

SECTION XV - REGULATORY INFORMATION

All ingredients are listed on the TSCA inventory
This product has been classified in accordance with the hazard criteria of the Canadian Controlled Product Regulations (CPR) and the MSDS contains all the information required by the CPR.

SECTION XVI - OTHER INFORMATION

NOTE: Films conforms to ASTM D-4236
All ingredients are listed on the TSCA inventory

Revision Information

Revised Sections Since Last Version:

Section XV - Regulatory Information

REVISION DATE: 08-JUN-1998

REPLACES SHEET DATED:

14-JAN-1998

COMPLETED BY: Polaroid Corp. Office of Health, Safety, & Environmental Affairs


This data is for guidance and is believed accurate as of the date of issue hereof. It is based upon information and tests believed to be reliable but suitability for any particular use should be confirmed by the user's own tests. The advice contained in this data sheet is given and accepted at the user's risk and Polaroid makes no guarantee of results and assumes no obligation or liability in connection herewith.

Data Sheet No. **M-0917**

Revision **I**

NFPA FIRE HAZARD SYMBOL

Drum Label Information



HAZARD SIGNAL WORD

WARNING

HAZARDS

CONTAINS ALKALI

Eye Contact May Cause Permanent Eye Damage.

Skin and Mouth Contact May Cause Irritation or Burns.

PRECAUTIONARY MEASURES

Do not get in eyes, on skin, mouth or clothing.

Wash thoroughly after handling

EMERGENCY AND FIRST AID PROCEDURES

In case of eye contact, immediately flush eyes with plenty of water for at least fifteen minutes. Remove contact lenses if worn. Seek Medical attention immediately.

In case of skin contact, flush affected area with plenty of water.

In case of oral contact rinse mouth immediately with plenty of water. Drink water or citrus juices to dilute or neutralize any alkali that may have been swallowed. Do NOT induce vomiting. Seek Medical attention immediately.

Get Medical attention immediately. If swallowed, do NOT induce vomiting unless directed to do so by Medical personnel. Never give anything by mouth to an unconscious person.

SPILL CONTROL:

Handle film so as not to break developer pods prior to film development.

Small quantities of developer fluid may be wiped up with a damp paper towel using care to avoid any skin or eye contact.

OTHER D.O.T. INFORMATION

Film product not regulated